

***Provider Data Import (PDI)***  
**Specifications Document**

Build 871

September 3, 2015

Copyright © 2009-2014 Jeff Murray's Programming Shop, Inc. (jProg). All rights reserved. Development of the Provider Data Import (PDI) and related functionality were funded by the Denver Mayor's Office of HIV Resources.

## I. Overview

The Provider Data Import (PDI) is designed to provide an easy 'intermediate step' in the complicated process of importing data from other applications into CAREWare. It utilizes an Access database to provide a standard format for data that the CAREWare business tier can then use to populate the CAREWare database. Thus a user can populate a few tables in an easy-to-use Access format and CAREWare will do the rest.

Update:

As of build ADAP1, the PDI can import data from an XML format in addition to the MDB file. The XML file uses the same data structure as the Access MDB.

### 1. The File

As a default, CAREWare will be configured to import MS Access 2000 database files, though the central site may alter a business tier setting that would allow other data formats. If applicable, the central site will provide a blank file that can be used as a template. That file will contain empty tables: *exp\_adap\_enrollment\_history*, *exp\_annual\_review*, *exp\_appointment*, *exp\_attachments*, *exp\_case\_note*, *exp\_client*, *exp\_counseling\_testing*, *exp\_custom\_subform*, *exp\_diagnosis*, *exp\_drug\_payment*, *exp\_eligibility*, *exp\_immunization*, *exp\_insurance\_assessment*, *exp\_map\_client\_provider*, *exp\_medication*, *exp\_poverty\_level\_assessment*, *exp\_pregnancy*, *exp\_provider*, *exp\_receipt*, *exp\_referral*, *exp\_relations*, *exp\_service*, *exp\_subservice*, *exp\_test*, *exp\_vital\_sign*. The relational structure of these tables is simple: *exp\_adap\_enrollment\_history*, *exp\_annual\_review*, *exp\_appointment*, *exp\_case\_note*, *exp\_counseling\_testing*, *exp\_custom\_subform*, *exp\_diagnosis*, *exp\_drug\_payment*, *exp\_eligibility*, *exp\_immunization*, *exp\_insurance\_assessment*, *exp\_map\_client\_provider*, *exp\_medication*, *exp\_poverty\_level\_assessment*, *exp\_pregnancy*, *exp\_referral*, *exp\_relations*, *exp\_service*, *exp\_test*, *exp\_vital\_sign* have foreign keys that refer to the primary key in *exp\_client*. Note that these tables have primary keys as well, even though these are not referenced by foreign keys in other tables. The table *exp\_provider*, which will contain basic information about the exporter, will not be a part of the relational structure.

The only requirement for filenames will be that they have the .mdb extension that is common for MS Access databases. However, the central site may require a site ID and an export date in the filename to make file management easier.

### 2. The Data

Exporters are recommended to include any record that was added, edited, or deleted since the most recent export. The export files can contain data from any range of dates, though

it will be important for the central site to be able to know the chronological sequence of the export files. The import process will add new records and edit or delete existing records based on rules for each record type. If there is an existing record based on these values it will be updated to match the incoming record. Otherwise, a new record will be added. An existing record will be deleted if it matches an existing one and the *is\_delete* field is set to 'yes'.

**CLIENT** records will be imported and matched based on the client's URN (this value is generated by CAREWare based on the client's first name, last name, gender, and DOB). An incoming client record that generates the URN of an existing client will be treated as the same client and the existing client record may be updated based on options chosen by the user running the import (see below).

*Note: The client's first and/or last names can be excluded from the client records if necessary, but Date of Birth (DOB) and Gender are always required. In this case the EURN (Encrypted URN) field for each client will be required, as it will be used to match existing clients instead of the URN. For help with generating valid EURN values:*

- See [Appendix A](#) for information and sample code for programmatically creating an EURN for clients.
- See [Appendix B](#) for information on using the access mdb template file to automatically create the EURNs.

Client records should be included if they have been added or edited since the last export OR if any other record related to that client is included (i.e., any service, referral, annual review, etc). Deletion of client records will not be handled through the export/import process.

**ADAP ENROLLMENT HISTORY** records the ADAP enrollment history of clients. This table is only used for ADAP provider domains. This table is matched to client, date, and domain.

**ANNUAL REVIEW** – This table has been entirely deprecated as of the 800+ builds of CAREWare. Data from this table will still be imported for historical purposes, but this table in CAREWare is no longer used. Insurance and poverty level data are now held on the tables *exp\_insurance\_assessment* and *exp\_poverty\_level\_assessment*. Annual Screening data will now be recorded as screenings on *exp\_test*. These data elements have been retained in *exp\_annual\_review* table but are deprecated; If used, they lose precedence over the corresponding data in the new areas. If there is an existing record, it may be updated based on options chosen by the user running the import (see below).

**APPOINTMENT** records will be matched on: client, domain, service type and date. An appointment will be considered a match if the date is within + or – 1 day of the date of the incoming record.

**ATTACHMENTS** records will be matched to attachment list, date, and domain

**CASENOTE** records will be matched on: client, date and domain. NOTE: If an existing case note is a match, the existing note will be overwritten, not appended to.

**COUNSELING AND TESTING** records will be matched on: client, test date, and domain.

**COUNTY RFT** provides a list of all county codes.

**DIAGNOSIS** records will be matched on: client, date, domain, and diagnosis code.

**DRUG PAYMENT** records will be matched on: client, date, domain, and NDC for drug overlaps. User can set a drug overlap days in the import settings to determine whether a drug is overlapped.

**ELIGIBILITY** records will be matched on: client, date, domain, and eligibility code.

**IMMUNIZATION** records will be matched on: client, date, domain, and immunization code.

**INSURANCE ASSESSMENT** records will be matched on: client, date and domain. If there is an existing record, its values are updated based on the options chosen by the user (mentioned in NOTE above). The values in *exp\_insurance\_assessment* take precedence over the values entered in the respective fields of *exp\_annual\_review*.

**MAP CLIENT PROVIDER** matches client PK's to a client-provider FK and the provider name.

**MEDICATION** records will be matched on: client, medication code, and a date span based on the start and end date of the incoming medication (a medication with no end date is considered to always be active). The import will search for medications whose active dates overlap the date span of the incoming medication record. Any matching records that are found will be treated as the same record and updated accordingly with the following exceptions:

- Start Date is only updated if the incoming value is BEFORE the existing one.
- End Date is only updated if the incoming value is AFTER the existing one.

**OWNERSHIP STATUS RFT** is a reference code defining what kind of organization the provider is.

**POVERTY LEVEL ASSESSMENT** records will be matched on client, date and domain. The values in *exp\_poverty\_level\_assessment* take precedence over those entered in the corresponding fields of *exp\_annual\_review*.

**PREGNANCY** records will be matched on: client, domain, and estimated conception date. If there is an existing record with an Estimated Conception date within 30 days of the incoming record, then this will be treated as the same record and updated accordingly.

**PROVIDER** links the import file to the provider domain in CAREWare during the import process. This record imports the provider data for funding sources, grantee information, and other information created using the setup wizard during the provider setup.

**PROVIDER TYPE RFT** provides pk's for types of providers mapped to the provider table

**RECEIPTS** records are tied to a specific service record and all receipts for a service will be synced to the incoming receipts for a service. Note that because of this behavior it is important to send all receipts for a service, not just new ones.

**REFERRAL** records will be matched on: client, date referred, (*referred from*) domain, service category, referred-to site.

**RELATIONS** records will be matched on: domain, index client, and dependant client.

**SERVICE** records will be matched based on: client, domain, service date, and subservice. Note regarding service contracts (optional field) - If there is a value in the *srv\_contract\_name* field, then this value **MUST** match to the name of a valid contract for the domain (a valid contract is one where the subservice is be active for the contract and the service date falls between the start and end dates of the contract). If no value is entered in the contract name, then there must be exactly one valid contract for the subservice and date of service.

**STATE RFT** provides the reference codes for all states

**SUBSERVICE** records the names of subservices and creates a pk for each

**TEST** records will be matched on: client, date, domain and test definition.

**TEST DEFINITION** records the names of test definitions and creates a pk for each.

**VERSION** records the version of this PDI template

**VERSION HISTORY** records changes made to this version of the PDI template

**VITAL SIGN** records will be matched to client, date, and domain.

## II. The File Format

Note that in the bulleted lists the Description/Comments column specifies what codes CAREWare uses for each value. Exporters are not *required* to use these codes, though using them would help to simplify the mapping process. Whatever values are used, it is very important that the exporters coordinate with the central importer to establish what codes will be used for what values and that the same values are consistently used. Failure to do this will result in incorrect data being imported.

NOTE: The state and county fields are exceptions to this, as they use designated FIPS codes. The available codes are included in the template file in the tables *exp\_state\_rft* and *exp\_county\_rft*.

### exp provider

Field Name	MS Access Data Type	Size	Req. ?	Old Name	Description/Comment
prv_name	Text	60	Yes	Prvname 1	The name of the provider
prv_part_a_provided	Yes/No	n/a	No*	Title1	Whether or not the provider receives Part A funds.
prv_part_a_prv_id	Text	4	No	Prvid	The Part A provider ID.
prv_part_b_provided	Yes/No	n/a	No*	Title2	Whether or not the provider receives Part B funds.
prv_part_b_prv_id	Text	4	No	Prvid	The Part B provider ID.
prv_part_a_grn_id	Text	4	No	Grantid	The Part A grantee ID.
prv_part_b_grn_id	Text	4	No	Grantid	The Part B grantee ID.
prv_part_c_provided	Yes/No	n/a	No*	Title3	Whether or not the provider receives Part C funds.
prv_part_c_grn_id	Text	14	No	Grantid	The Part C grantee ID.
prv_part_d_provided	Yes/No	n/a	No*	Title4	Whether or not the provider receives Part D funds.
prv_part_d_grn_id	Text	14	No	Grantid	The Part D grantee ID.
prv_street	Text	60	No	Prvaddr1	Provider's street address
prv_city	Text	25	No	Prvcity	Provider's city
prv_state	Text	2	No	State	Value must be a key from exp_state_rft (FIPS code)
prv_zip	Text	9	No	Zip & Zip4	Provider's zipcode
prv_contact_name	Text	30	No	Contname	Contact staff for provider
prv_contact_title	Text	30	No	Conttitl	Contact staff for provider's title
prv_contact_phone	Text	25	No	Phone	Contact staff for provider's phone number
prv_contact_fax	Text	25	No	Fax	Contact staff for provider's fax number
prv_contact_email	Text	35	No	Email	Contact staff for provider's email address

prv_qa_rep_name	Text	30	No	-	Name of the provider's quality assurance representative.
prv_qa_rep_email	Text	35	No	-	Email of the provider's quality assurance representative.
prv_taxpayer_id	Text	9	No	Taxid	
prv_provider_type	Text	2	No	Prvtype	Code for: <ul style="list-style-type: none"> <li>• 01 - Hospital or hospital-based client</li> <li>• 02 - Publicly-funded Community Health Center</li> <li>• 03 - Publicly-funded Community Mental Health Center</li> <li>• 04 - Other Community-based Service Organization (CBO)</li> <li>• 05 - Health Department</li> <li>• 06 - Substance abuse treatment center</li> <li>• 07 - Solo/Group Private Medical Practice</li> <li>• 08 - Agency Reporting for Multiple Fee-for-Service Providers</li> <li>• 09 - PLWHA coalition</li> <li>• 10 - VA facility</li> <li>• 11 - Other facility</li> <li>• 12 - HL7 Import Provider</li> </ul>
prv_reporting_scope	Text	1	No	?	A legacy CADR field that remains in the Provider Setup Wizard. Code for: <ul style="list-style-type: none"> <li>• 1 - ALL Clients receiving a service ELIGIBLE for Title 1 or 2 funding</li> <li>• 2 - ONLY Clients receiving a Title 1 or 2 FUNDED service</li> </ul>
prv_ownership_status	Text	2	No	Owner	Code for: <ul style="list-style-type: none"> <li>• 1 - Public/Local</li> <li>• 2 - Public/State</li> <li>• 3 - Public/Federal</li> <li>• 4 - Private, Non-profit (not faith-based)</li> <li>• 5 - Private, For-profit</li> <li>• 6 - Unincorporated</li> <li>• 7 - Faith-based organization</li> <li>• 8 - Other</li> </ul>
prv_num_paid_staff	Single	n/a	No	Paidstaf	Total paid HIV staff in FTEs.

prv_num_volunteers	Single	n/a	No	Volstaff	Total paid volunteer staff in FTEs.
prv_minority_board	Yes/No	n/a	No*	RaceBrd	Yes if racial/ethnic minority group members make up greater than 50% of your agency's board members.
prv_minority_staff	Yes/No	n/a	No*	Racestf	Yes if racial/ethnic minority group members make up greater than 50% of your agency's professional staff members in HIV direct services.
prv_minority_clinicians	Yes/No	n/a	No*	Racesolo	Yes if your agency is a solo or group private health care practice in which greater than 50% of the clinicians are racial/ethnic minority group members.
prv_minority_served	Yes/No	n/a	No*	Tradprv	Yes if your agency is a traditional provider that has historically served racial/ethnic minority patients/clients but does not meet the criteria in the fields above.
prv_minority_other	Yes/No	n/a	No*	Othprv	Yes if your agency does not meet the criteria of any of the four preceding fields.
prv_receives_330_funding	Text	20	No	-	Code for: <ul style="list-style-type: none"> <li>• 0 – No</li> <li>• 1 – Yes</li> <li>• 9 - Unknown</li> </ul>
prv_receives_Mai_funding	Text	20	No	-	Code for: <ul style="list-style-type: none"> <li>• 0 – No</li> <li>• 1 – Yes</li> <li>• 9 - Unknown</li> </ul>
prv_other_provider_type	Text	50	No	-	Allows for specification of what provider type is when 'other' is chosen for prv_provider_type
prv_other_owner_status	Text	50	No	-	Allows for specification of what ownership status is when 'other' is chosen for prv_ownership_status

### exp\_client

Note: an exp\_client record must be included for any associated record in the file, even if the client record itself has not changed since the last export.

Field Name	MS Access Data Type	Size	Req. ?	Old Name	Description/Comment
cln_pk	Text	38	Yes	PK	Used only for database relations within this file.

cln_urn	Text	20	No*	Urn	Encrypted URN (usually nine characters). Required if cln_first_name or cln_last_name is blank.
cln_urn_suffix	Text	1	No***		Used to distinguish multiple clients with the same URN.
cln_client_id	Text	16	No	-	Domain specific identification field for clients.
cln_last_name	Text	40	No	Lname	
cln_first_name	Text	25	No	Fname	
cln_middle_name	Text	25	No	Minit	New field holds 25 characters, but initial is acceptable.
cln_street	Text	50	No	-	
cln_city	Text	30	No	-	
cln_state	Text	2	No	-	FIPS code for the state.
cln_county	Text	4	No	-	FIPS code for the county. Must be a valid county code for the given State. If no state is given then this must be null as well.
cln_zip	Text	10	No	Clntzip	Client Zip code
cln_phone	Text	25	No	-	Client Phone
cln_dob	Date/Time	n/a	Yes	Bmonth, Bday, Byear	Full DOB is required.
cln_dob_estimated	Yes/No	n/a	No	-	Signifies whether or not the DOB is an estimate.
cln_gender	Text	20	Yes	Sex	Code for: <ul style="list-style-type: none"> <li>• 1 - Male</li> <li>• 2 - Female</li> <li>• 3 - Transgender</li> <li>• 4 - Transgender MtF</li> <li>• 5 - Transgender FtM</li> <li>• 6 - Refused to Report</li> <li>• 9 - Unknown</li> </ul>
cln_race_white	Yes/No	n/a	No*	White	
cln_race_black	Yes/No	n/a	No*	Black	
cln_race_asian	Yes/No	n/a	No*	Asian	
cln_race_pacific	Yes/No	n/a	No*	Pacisl	
cln_race_indian	Yes/No	n/a	No*	Natamer	
cln_race_other	Yes/No	n/a	No*	Othrace	
cln_race_unknown	Yes/No	n/a	No*	unkrace	
cln_hispanic	Text	20	No**	Hispanic	Code for: <ul style="list-style-type: none"> <li>• 0 - No</li> <li>• 1 - Yes</li> <li>• 9 - Unknown</li> </ul>
cln_risk_msm	Yes/No	n/a	No*	Hivrisk <1-4>	Men who have Sex with Men; now a separate Boolean value.
cln_risk_idu	Yes/No	n/a	No*	Hivrisk <1-4>	Intravenous Drug Use; now a separate Boolean value.
cln_risk_hetero	Yes/No	n/a	No*	Hivrisk <1-4>	Heterosexual contact; now a separate Boolean value.

cln_risk_hemo	Yes/No	n/a	No*	Hivrisk <1-4>	Hemophilia/coagulation disorder; now a separate Boolean value.
cln_risk_perinatal	Yes/No	n/a	No*	Hivrisk <1-4>	Perinatal transmission; now a separate Boolean value.
cln_risk_transfusion	Yes/No	n/a	No*	Hivrisk <1-4>	Receipt of transfusion of blood, blood components, or tissue; now a separate Boolean value.
cln_risk_other	Yes/No	n/a	No*	Hivrisk <1-4>	Now a separate Boolean value.
cln_risk_other_description	Text	40	No		Description of the "other" risk; now a separate Boolean value.
cln_risk_unknown	Yes/No	n/a	No*	Hivrisk <1-4>	Now a separate Boolean value.
cln_vital_status	Text	20	No**	Vitalst	Code for: <ul style="list-style-type: none"> <li>• 1 - Alive</li> <li>• 3 - Deceased</li> <li>• 4 - Unknown</li> </ul> Enrollment Status now a separate value.
cln_date_of_death	Date/Time	n/a	No	Dod	
cln_enrollment_status	Text	20	No**	Vitalst	Code for: <ul style="list-style-type: none"> <li>• 1 – Active</li> <li>• 2 – Inactive/Case Closed (deprecated)</li> <li>• 3 – Referred or Discharged</li> <li>• 4 – Removed</li> <li>• 5 - Incarcerated</li> <li>• 6 - Relocated</li> <li>• 9 - Unknown (deprecated)</li> </ul>
cln_enrollment_date	Date/Time	n/a	No	Enrldate	Date of client's first enrollment.
cln_date_case_closed	Date/Time	n/a	No	Enddate	Case closed date
cln_hiv_status	Text	20	No **	Hivstat	Code for: <ul style="list-style-type: none"> <li>• 1 - HIV-positive (not AIDS)</li> <li>• 2 - HIV-positive (AIDS status unknown),</li> <li>• 3 - CDC defined AIDS,</li> <li>• 4 - HIV-negative (affected),</li> <li>• 5 - HIV-indeterminate, or</li> <li>• 9 – Unknown (deprecated)</li> </ul>
cln_hiv_date	Date/Time	n/a	No	-	The date on which the client was diagnosed HIV+.
cln_hiv_date_est	Yes/No	n/a	No*	-	Yes if the HIV+ date is an estimate.

cln_aids_date	Date/Time	n/a	No	-	The date on which the client was diagnosed with AIDS.
cln_aids_date_est	Yes/No	n/a	No*	-	Yes if the AIDS date is an estimate.
cln_date_art_first_prescribed	Date/Time	n/a	No	-	Date client was first prescribed ARV medications.
cln_pre_art_reason	Text	20	No	-	Code for explanation of why client was not prescribed ART after diagnosed with HIV: <ul style="list-style-type: none"> <li>• 1 - Treatment not medically indicated per guidelines,</li> <li>• 2 - Client not ready (as determined by clinician),</li> <li>• 3 - Client refused therapy, or</li> <li>• 4 - Other extenuating circumstances (e.g. inadequate insurance, ability to pay)</li> </ul>
cln_med_allergies	Text	255	No	-	Free text description of any allergies to medications.
cln_notes	Memo	n/a	No	-	Free text for additional client notes
cln_encrypted_UCI	Text	50	No	-	If URN fields are supplied then this value is not used (it is generated from the URN).
cln_adap_application_date	Date/Time	n/a	No		Date of received ADAP application
cln_race_label	Text	50	No	-	Alternate method for importing Race. This text value will be mapped to one or more values for Race during import.
cln_risk_label	Text	50	No	-	Alternate method for importing Risk Factors. This text value will be mapped to one or more values for Risk Factors during import.
cln_birth_gender	Text	20	No		Gender at birth. Code for: <ul style="list-style-type: none"> <li>• 1 - Male</li> <li>• 2 - Female</li> </ul>
cln_hispanic_subgroup	Text	50	No		Only imported if cln_hispanic = "1". Code for: <ul style="list-style-type: none"> <li>• 1 – Mexican, Mexican American, Chicano/a</li> <li>• 2 - Puerto Rican</li> <li>• 3 - Cuban</li> <li>• 4 – Another Hispanic, Latino/a or Spanish origin</li> </ul> **** See Note below

cln_pacific_subgroup	Text	50	No		Only imported if cln_race_pacific = Yes. Code for: <ul style="list-style-type: none"> <li>● 1 – Native Hawaiian</li> <li>● 2 – Guamanian or Chamorro</li> <li>● 3 - Samoan</li> <li>● 4 - Other Pacific Islander</li> </ul> **** See Note below
cln_asian_subgroup	Text	50	No		Only imported if cln_race_asian = Yes. Code for: <ul style="list-style-type: none"> <li>● 1 – Asian Indian</li> <li>● 2 - Chinese</li> <li>● 3 – Filipino</li> <li>● 4 – Japanese</li> <li>● 5 – Korean</li> <li>● 6 – Vietnamese</li> <li>● 7 – Other Asian</li> </ul> **** See Note below

\* All Boolean fields are required by CAREWare. Any left null will be interpreted as FALSE.

\*\* CAREWare dropdown lists that specify an Unknown option do not permit null values. Any left null will be interpreted as “Unknown.”

\*\*\* Null value will default to ‘U’

\*\*\*\*These are placeholder positions. For each racial subgroup that is true place a “1” and for each racial subgroup that is false place a “0”. (I. e., a client is Puerto Rican and Cuban. You will place a 0110 in the Hispanic Subgroup column.)

### **exp\_counseling\_testing**

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
cns_ts_pk	Text	38	No	Primary key for the record that must be unique.
cns_ts_cln_fk	Text	38	No	Foreign key to the cw_client table.
cns_ts_pre_counsel	Text	20	No	Indicates whether or not there was pretest counseling.
cns_ts_pre_counsel_date	Date/Time	n/a	No	Date of pretest counseling.
cns_ts_post_counsel	Text	20	No	Indicates whether or not there was post-test counseling.
cns_ts_post_counsel_date	Date/Time	n/a	No	Date of post-test counseling.
cns_ts_reason_no_post_counsel	Text	50	No	The reason the client was not given post-test counseling.
cns_ts_post_counsel_referred	Yes/No	n/a	No	Indicates whether or not there was post-test counseling.
cns_ts_hiv_tested	Text	20	No	Indicates whether or not the client was HIV tested.

cns_ts_hiv_tested_label	Text	50	No	Descriptive text for whether or not HIV testing was completed
cns_ts_hiv_tested_result	Text	20	No	The results of HIV testing
cns_ts_hiv_tested_result_label	Text	50	No	Descriptive text for the results of HIV testing
cns_ts_hiv_tested_date	Date/Time	n/a	No	Date of the HIV test.
cns_ts_pn_offered	Text	20	No	Indicates whether or not the client was offered partner notification services.
cns_ts_pn_offered_label	Text	50	No	Descriptive text for whether or not the client was offered partner notification services.
cns_ts_pn_number	Number	n/a	No	The number of partners notified.
cns_ts_comment	Text	255	No	Additional comments added by the user.
cns_ts_delete	Yes/No	n/a	No	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
cns_ts_pre_counsel_label	Text	50	No	Descriptive text for whether or not there was pretest counseling.
cns_ts_post_counsel_label	Text	50	No	Descriptive text for whether or not there was post-test counseling.

### exp adap enrollment history

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
adp_en_hs_pk	Text	38	No	Uniquely identifies each record.
adp_en_hs_cln_fk	Text	38	No	Points to the client record to which this record is related
adp_en_hs_date	Date/Time	n/a	No	Date of enrollment update
adp_en_hs_status_code	Text	38	No	Code for current enrollment status: <ul style="list-style-type: none"> <li>• 01 - Enrolled, receiving services</li> <li>• 02 - Enrolled, on waiting list</li> <li>• 03 - Enrolled, services not requested</li> <li>• 04 - Disenrolled</li> <li>• 05 - Legacy Enrolled</li> <li>• 06 - Legacy Disenrolled</li> </ul> NOTE: 05 and 06 are only for historical purposes. These are not valid values for current data.
adp_en_hs_status_label	Text	100	No	Descriptive label for status code
adp_en_hs_disenroll_code	Text	38	No	Code for disenrollment reason: <ul style="list-style-type: none"> <li>• 01 - Ineligible, change in ADAP program FPL requirements</li> <li>• 02 - Ineligible for ADAP, now eligible for Medicaid</li> <li>• 03 - Ineligible, other reason</li> </ul>

				<ul style="list-style-type: none"> <li>• 04 - Did not recertify</li> <li>• 05 - Did not fill prescription</li> <li>• 06 - Deceased</li> <li>• 07- Dropped out, no reason given</li> <li>• 08 - Other/Unknown</li> </ul>
adp_en_hs_disenroll_label	Text	100	No	Descriptive text for disenrollment reason
adp_en_hs_other_disenroll_code	Text	38	No	Code for other disenrollment reason
adp_en_hs_other_disenroll_label	Text	100	No	Descriptive text for other disenrollment reason
adp_en_hs_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.

**exp annual review (DEPRECATED)**

Field Name	MS Access Data Type	Size	Req. ?	Old Name	Description/Comment
ann_rv_pk	Text	38	Yes	-	Not used by the import process; only useful for user reference.
ann_rv_cln_fk	Text	38	Yes	-	Points to the client record to which this record is related.
ann_rv_year	Text	4	Yes	-	4 digit year to which this annual review applies.
ann_rv_household_size	Integer	n/a	No	Hhsize	DEPRECATED 1-9999
ann_rv_household_income	Currency	n/a	No	Hhinc	DEPRECATED \$0.00 - \$999,999,999.99
ann_rv_housing_arrangement	Text	2	No*	Nohome	DEPRECATED Code for: <ul style="list-style-type: none"> <li>• 0 - Permanently Housed</li> <li>• 1 - Non-permanently Housed</li> <li>• 2 - Institution</li> <li>• 3 - Other</li> <li>• 9 -Unknown/Unreported</li> </ul>
ann_rv_insurance_type	Text	2	No*	Primpay	DEPRECATED Code for: <ul style="list-style-type: none"> <li>• 1 - Private</li> <li>• 2 - Medicare</li> <li>• 3 - Medicaid</li> <li>• 4 - Other public (e.g. Campus, VA)</li> <li>• 5 - No Insurance</li> <li>• 6 - Other</li> <li>• 9 - Unknown</li> </ul>
ann_rv_medical_care	Text	2	No*	Primcare	DEPRECATED Code for:

					<ul style="list-style-type: none"> <li>• 1 - Publicly-funded clinic or health dept.</li> <li>• 2 - Private practice</li> <li>• 3 - Hospital outpatient center</li> <li>• 4 - Emergency Room</li> <li>• 5 - No primary source of care</li> <li>• 8 - Other</li> <li>• 9 - Unknown</li> </ul>
ann_rv_q*_substance_abuse_history	Text	1	Yes	Subhxq <1-4>	Code for: <ul style="list-style-type: none"> <li>• 0 - No</li> <li>• 1 - Yes, active history within last 3 months</li> <li>• 2 - Yes, but not active within last 3 months</li> </ul>
ann_rv_q*_substance_abuse_treatment	Text	2	Yes	Subtrq <1-4>	Code for: <ul style="list-style-type: none"> <li>• 01 - In Treatment</li> <li>• 02 - Waiting list for treatment</li> <li>• 03 - Refused Treatment</li> <li>• 04 - Completed Treatment</li> <li>• 05 - Pre-treatment process</li> <li>• 06 - Dropped out of treatment</li> <li>• 07 - No active treatment or counseling</li> <li>• 08 - Other</li> <li>• 88 - Not applicable</li> </ul>
ann_rv_q*_mental_health_history	Text	1	Yes	Mhxxq <1-4>	Code for: <ul style="list-style-type: none"> <li>• 0 - No</li> <li>• 1 - Yes, active history within last 3 months</li> <li>• 2 - Yes, but not active within last 3 months</li> </ul>
ann_rv_q*_mental_health_treatment	Text	2	Yes	Mhtrq <1-4>	Code for: <ul style="list-style-type: none"> <li>• 01 - In Treatment</li> <li>• 02 - Waiting list for treatment</li> <li>• 03 - Refused Treatment</li> <li>• 04 - Completed Treatment</li> <li>• 05 - Pre-treatment process</li> <li>• 06 - Dropped out of treatment</li> <li>• 07 - No active treatment or counseling</li> <li>• 08 - Other</li> <li>• 88 - Not applicable</li> </ul>

ann_rv_ins_tp_private	Yes/No	n/a	No*	-	DEPRECATED Adds private insurance as other insurance
ann_rv_ins_tp_medicare	Yes/No	n/a	No*	-	DEPRECATED Adds Medicare insurance as other insurance
ann_rv_ins_tp_medicaid	Yes/No	n/a	No*	-	DEPRECATED Adds Medicaid insurance as other insurance
ann_rv_ins_tp_other_public	Yes/No	n/a	No*	-	DEPRECATED Adds Other Public insurance as other insurance
ann_rv_ins_tp_no_insurance	Yes/No	n/a	No*	-	DEPRECATED Adds No insurance as other insurance.
ann_rv_ins_tp_other	Yes/No	n/a	No*	-	DEPRECATED Adds Other insurance as other insurance
ann_rv_ins_tp_unknown	Yes/No	n/a	No*	-	DEPRECATED Adds Unknown insurance as other insurance
ann_rv_other_insurance	Text	50	No	-	DEPRECATED Allows specification of other insurance if ann_rv_ins_tp_other is chosen
ann_rv_mental_health_yes_nmi_rfk	Text	2	No	-	DEPRECATED Code for: <ul style="list-style-type: none"> <li>• 0 – No</li> <li>• 1 – Yes</li> <li>• 2 – Not Medically Indicated</li> <li>• 9 - Unknown</li> </ul>
ann_rv_sub_abuse_yes_nmi_rfk	Text	2	No	-	DEPRECATED Code for: <ul style="list-style-type: none"> <li>• 0 – No</li> <li>• 1 – Yes</li> <li>• 2 – Not Medically Indicated</li> <li>• 9 - Unknown</li> </ul>
ann_rv_hiv_counseled	Yes/No	n/a	No*	-	DEPRECATED Yes if this client was HIV Counseled for this review year
ann_rv_counseled_by	Text	50	No	-	DEPRECATED Code for: <ul style="list-style-type: none"> <li>• 1 – Primary care clinician</li> <li>• 2 – Case mgr/social worker</li> <li>• 3 – Other trained counselor</li> <li>• 9 – Unknown</li> </ul>

**exp appointment**

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
app_pk	Text	50	No	Uniquely identifies each record.
app_cln_fk	Text	38	Yes	Points to the client record to which this record is related.

app_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
app_date	Date/time	n/a	Yes	Date of the appointment.
app_amount	Currency	n/a	No	Amount of any payment collected.
app_employee	Text	38	No	Employee creating the appointment.
app_comment	Memo	n/a	No	Free text used to supply additional information.
app_sent_to_employee	Text	38	No	Employee the client was sent to contact.
app_subservice	Text	38	Yes	Service which is the purpose of the appointment.
app_employee_label	Text	100	No	Descriptive label to help with matching.
app_sent_to_employee_label	Text	100	No	Descriptive label to help with matching.
app_subservice_label	Text	100	No	Descriptive label to help with matching.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.

### exp attachments

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
att_pk	Text	36	No	Uniquely identifies each record.
att_att_ls_fk	Text	38	Yes	
att_file_name	Text	255	No*	
att_cnt_tp_label	Text	35	Yes	Date the note was entered.
att_comment	Text	100	No	Comments on this attachment.
att_file_date	Date/Time	n/a	No	
att_attach_date	Date/Time	100	No	
att_file_type	Text	5	No	

### exp case note

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
cas_nt_pk	Text	38	Yes	Uniquely identifies each record.
cas_nt_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
cas_nt_date	Date/Time	n/a	Yes	Date the note was entered.
cas_nt_note	Memo	n/a	Yes	Text of the note.
cas_nt_employee	Text	38	No	Employee entering this case note.
cas_nt_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare
cas_nt_employee_label	Text	100	No	Descriptive label to help with matching.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file;

				prv_name acts as a referential key to the provider for each record.
--	--	--	--	---

### exp diagnosis

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
dgn_pk	Text	38	No	Uniquely identifies each record.
dgn_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
dgn_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
dgn_definition_code	Text	38	Yes	Code for the specific diagnosis. The master list is created and maintained by the central administrator.
dgn_assessment	Text	20	No	Code for: <ul style="list-style-type: none"> <li>• 1 - Definitive</li> <li>• 2 - Presumptive</li> <li>• 3 - Unknown</li> </ul>
dgn_date	Date/Time	n/a	Yes	Date the diagnosis was given
dgn_comment	Text	255	No	Free text that can be used to supply additional information about the diagnosis.
dgn_definition_name	Memo	n/a	No	Descriptive label for diagnosis code, primarily used in the CAREWare PDE
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
dgn_problem	Text	75		Medical issue resulting in diagnosis
dgn_problem_status	Text	50		Status of client's problem
dgn_date_resolved	Date/Time	N/A		Date of when problem was resolved
dgn_date_icd10_code	Text	7		ICD-10 diagnosis code

### exp drug payment

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
drg_py_pk	Text	38	No	Uniquely identifies each record.
drg_py_delete	Yes/No	n/a	No	Yes if this record has been deleted at the provider and should be deleted in CAREWare. Null value is false.
drg_py_cln_fk	Text	38	No	Points to the client record to which this record is related.
drg_py_ndc	Text	11	No	Standardized NDC
drg_py_date	Date/Time	38	Yes	Date of disbursement
drg_py_quantity	Number	n/a	No	Must be <> 0 (a negative value is an adjustment)

drg_py_unit_price	Currency	n/a	No*	Must be >= 0. If null, will be calculated from total. (This should be null if total is supplied)
drg_py_total	Currency	n/a	No*	Defaults to 0 if total and unit price are Null. If total is null and unit price is supplied, this will be calculated from unit price and quantity.
drg_py_dispenser_code	Text	38	No	Unique key identifying the dispenser for this record.
drg_py_dispenser_label	Text	50	No	Descriptive label to help with mapping dispensers.
drg_py_funding_code	Text	38	No	Unique key identifying the drug funding.
drg_py_insurance_code	Text	38	No	Client's reported insurance type for this disbursement.
drg_py_funding_label	Text	50	No	Descriptive label to help with mapping drug funding.
drg_py_insurance_label	Text	50	No	Descriptive insurance type label for this disbursement.
drg_py_comments	Text	255	No	Place any comments you have about the drug payment here
drg_py_dispense_fee	Currency	n/a	No	Dispensing fee for this disbursement.
drg_py_duration	Number	n/a	No	Number of days covered by this disbursement.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.

\* - Either unit price OR total should be supplied. If both have values, then unit price will be ignored and will be calculated from total and quantity during import.

NDC values will not be mapped; these are expected to be the correct standardized NDC. Records without a valid NDC will be flagged with the appropriate error code. Note that a given NDC must be active in the CAREWare formulary in order to be valid for import.

### exp\_eligibility

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
Elg_pk	Text	38	Yes	Uniquely identifies each record.
Elg_cln_fk	Text	38	No	Yes if this record has been deleted at the provider and should be deleted in CAREWare. Null value is false.
Elg_date	Date/Time	38	No	Date of change to client's eligibility status
elg_yes_no_code	Text	20	No	Eligibility status confirmation reference code
elg_yes_no_label	Text	50	Yes	Descriptive label for confirmation
elg_elg_cs_code	Text	20	No	Eligibility status custom reference code
elg_elg_cs_label	Text	50	No	Descriptive label for custom fields

elg_comment	Text	255	No	Any comments the user wishes to enter.
elg_delete	Yes/No	N/A	No	
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
elg_fnd_sr_code	Text	36	No	Eligibility status funding reference code
elg_fnd_sr_label	Text	50	No	Descriptive label for funding source

### exp immunization

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
imm_pk	Text	38	No	Uniquely identifies each record.
imm_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
imm_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
imm_definition_code	Text	38	Yes	Code for the specific diagnosis. The master list is created and maintained by the central administrator.
imm_received_code	Text	20	Yes	Determines whether the immunization was given. CAREWare values: <ul style="list-style-type: none"> <li>• 1 - Yes</li> <li>• 2 - NMI</li> <li>• 3 - No</li> <li>• 4 - Refused</li> </ul>
imm_date	Date/Time	n/a	Yes	Date the immunization was given
imm_immunity_code	Text	20	No	Code for any immunity: <ul style="list-style-type: none"> <li>• 01 - Immune</li> <li>• 02 - Nonimmune</li> <li>• 03 - History of infection</li> <li>• 04 - History of vaccination</li> <li>• 99 - Unknown</li> </ul>
Imm_label	Text	50	No	Identifying label

### exp insurance assessment

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
ins_as_pk	Text	38	No	Uniquely identifies each record.
ins_as_primary_insurance_code	Text	38	No	Primary Insurance for the client. Codes are: <ul style="list-style-type: none"> <li>• 1 Private (Deprecated)</li> <li>• 2 Medicare (unspecified)</li> <li>• 3 Medicaid</li> <li>• 4 Other public (e.g. Campus, VA)</li> </ul>

				<ul style="list-style-type: none"> <li>• 5 No Insurance</li> <li>• 6 Other</li> <li>• 9 Unknown</li> <li>• 7 Medicare Part A/B</li> <li>• 8 Medicare Part D</li> <li>• 10 Private - Employer</li> <li>• 11 Private - Individual</li> <li>• 13 VA, Tricare and other military health care</li> <li>• 14 IHS</li> </ul>
Ins_as_ins_tp_private	Yes/No	n/a	No*	DEPRECATED Adds private insurance as other insurance
Ins_as_ins_tp_medicare	Yes/No	n/a	No*	Adds Medicare insurance as other insurance
Ins_as_ins_tp_medicaid	Yes/No	n/a	No*	Adds Medicaid insurance as other insurance
Ins_as_ins_tp_other_public	Yes/No	n/a	No*	Adds Other Public insurance as other insurance
Ins_as_ins_tp_no_insurance	Yes/No	n/a	No*	Adds No insurance as other insurance.
Ins_as_ins_tp_other	Yes/No	n/a	No*	Adds other insurance as other insurance
Ins_as_ins_tp_unknown	Yes/No	n/a	No*	Adds unknown insurance as other insurance
Ins_as_other_insurance	Text	50	No	Stores the value of the 'other' insurance if 'ins_as_ins_tp_other' is chosen
Ins_as_date	Date/Time	n/a	Yes	Date the insurance record was added
Ins_as_cln_fk	Text	38	Yes	Points to the client record to which this record is related
Ins_tp_primary_insurance_label	Text	75	No	The client's Primary Insurance. This label field is not required, but the code field is (see above).
ins_as_ins_tp_medicare_ab	Yes/No	n/a	No	Adds Medicare insurance part A/B
ins_as_ins_tp_medicare_d	Yes/No	n/a	No	Adds Medicare insurance part D
Ins_as_delete	Yes/No	n/a	No	If set, it will delete the record
Ins_as_full_lis	Yes/No	n/a	No	With Medicare Part D Checked Full LIS Secondary Insurance
Ins_as_high_risk_pool	Yes/No	n/a	No	
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
Ins_as_ins_tp_private_ind	Yes/No	n/a	No	Adds Private – Individual as other insurance.
Ins_as_ins_tp_private_emp	Yes/No	n/a	No	Adds Private - Employer as other insurance.

Ins_as_ins_tp_va_military	Yes/No	n/a	No	Adds VA-military as other insurance.
Ins_as_ins_ihs	Yes/No	n/a	No	Adds Indian Health Services as other insurance.

### exp\_medication

Field Name	MS Access Data Type	Size	Req. ?	Description/Comment
mdc_pk	Text	38	Yes	Uniquely identifies each record.
mdc_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
mdc_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
mdc_medication_code	Text	120	Yes	Code for the description of the medication provided. The master list is created and maintained by the Central Administrator.
mdc_units	Number	n/a	No	Number of does given
mdc_strength	Number	n/a	No	Strength of each does
mdc_frequency	Text	20	No	Code for (See <a href="#">Appendix C</a> for a description of codes): <ul style="list-style-type: none"> <li>• 01 – qd</li> <li>• 02 – bid</li> <li>• 03 – tid</li> <li>• 04 – qid</li> <li>• 05 – prn</li> <li>• 06 – qw</li> <li>• 07 – biw</li> <li>• 08 – tiw</li> <li>• 09 – qow</li> <li>• 10 – qod</li> <li>• 11 – qh</li> <li>• 12 – qhs</li> <li>• 13 – qm</li> <li>• 14 – q6h</li> <li>• 15 – q12h</li> </ul>
mdc_start_date	Date/Time	n/a	Yes	Date medication started for client
mdc_end_date	Date/Time	n/a	No	Null for continuing medication.
mdc_indication	Text	20	No	Code for: <ul style="list-style-type: none"> <li>• 01 – ART</li> <li>• 02 – OI Prophylaxis</li> <li>• 03 – OI Treatment</li> <li>• 99 - Other</li> </ul>
mdc_prophylaxis	Text	20	No	Code for: <ul style="list-style-type: none"> <li>• 01 – Pneumocystis carinii pneumonia (PCP)</li> <li>• 02 – M. avium complex (mac)</li> <li>• 03 – M. tuberculosis (Mtb)</li> <li>• 04 – Candida</li> <li>• 05 – Cytomegalovirus (CMV)</li> <li>• 06 – Toxoplasma gondii</li> </ul>

				<ul style="list-style-type: none"> <li>• 07 – Varicella zoster virus (VZV)</li> <li>• 08 - Other</li> </ul>
mdc_discontinue_reason	Text	20	No	Code for: <ul style="list-style-type: none"> <li>• 01 - Virologic Failure</li> <li>• 02 - Toxicity</li> <li>• 03 - Intolerance</li> <li>• 04 - Lost to followup</li> <li>• 05 - Dose Change</li> <li>• 06 - Other</li> <li>• 09 - Unknown</li> <li>• 07 - Therapy completed</li> <li>• 08 - Improved immune function</li> <li>• 10 - Stock out/supply disruption</li> <li>• 11 - Managed treatment interruption</li> <li>• 12 - Non-adherent</li> <li>• 13 - Immunologic Failure</li> <li>• 14 - Pregnant</li> <li>• 15 - Risk of Pregnancy</li> <li>• 16 - Newly diagnosed TB</li> <li>• 17 - Availability of New Drug</li> <li>• 18 - Illness or hospitalization</li> <li>• 19 - Patient lacks sufficient financial resource</li> <li>• 20 - Patient decision</li> </ul>
mdc_comment	Text	50	No	Free text that can be used to supply additional information about the medication.
mdc_medication_label	Text	50	No	Descriptive label for medication code, primarily used in the CAREWare PDE.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
mdc_instructions	Text	35	No	Instruction for client's medication

**exp poverty level assessment**

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
pvr_lv_pk	Text	38	Yes	Uniquely identifies each record.
Pvr_lv_household_income	currency	n/a	no	1-9999
Pvr_lv_household_size	number	n/a	No	\$0.00 - \$999,999,999.99
Pvr_lv_date	Date/Time	n/a	yes	Date the poverty level record was added
Pvr_lv_cln_fk	Text	38	yes	Points to the client record to which this record is related
Pvr_lv_delete	Yes/No	n/a	No*	If set, it deletes poverty level record

prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
----------	------	----	----	---

### exp pregnancy

Fieldname	MS Access Data Type	Size	Req.?	Description/Comment
prg_pk	Text	38	Yes	Not used by the import process; only useful for user reference.
prg_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
prg_delete	Yes/No	n/a	No*	Yes if this record should be deleted.
prg_est_conception_date	Date/Time	n/a	Yes	Estimated date of conception.
prg_pn_care_date	Date/Time	n/a	No	Date prenatal care began for this pregnancy.
prg_pn_visits	Number	n/a	No	Number of prenatal visits during this pregnancy.
prg_pn_art_counsel	Text	20	No	Was client counseled for ART? Code for: <ul style="list-style-type: none"> <li>• 0 - No</li> <li>• 1 - yes</li> <li>• 9 - Unknown</li> </ul>
prg_pn_art_offered	Text	20	No	Was ART offered to the client? Code for: <ul style="list-style-type: none"> <li>• 0 - No</li> <li>• 1 - yes</li> <li>• 9 - Unknown</li> </ul>
prg_pn_art_taken	Text	20	No	Was ART taken? Code for: <ul style="list-style-type: none"> <li>• 0 - No</li> <li>• 1 - yes</li> <li>• 9 - Unknown</li> </ul>
prg_pn_art_date	Date/Time	n/a	No	Date ART was started. Should only have a value if prg_pn_art_taken = 'yes'
prg_outcome	Text	20	No	Code for: <ul style="list-style-type: none"> <li>• 01 - Live Birth</li> <li>• 02 - Therapeutic (induced) abortion</li> <li>• 03 - Spontaneous abortion (miscarriage)</li> <li>• 04 - Stillbirth</li> <li>• 05 - Unknown</li> </ul>
prg_delivery_date	Date/Time	n/a	No	
prg_newborn_status	Text	20	No	HIV Status of newborn. Code for: <ul style="list-style-type: none"> <li>• 0 - Negative</li> <li>• 1 - Positive</li> <li>• 2 - Indeterminate</li> <li>• 9 - Unknown/unreported</li> </ul>

prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
----------	------	----	----	---

### exp\_receipt

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
rcp_pk	Text	38	Yes	Primary key for the record that must be unique.
rcp_srv_fk	Text	38	No	Foreign key to the cw_service table.
rcp_date	Date/Time	n/a	No	The date of the receipt.
rcp_source	Text	50	No	Indicates who paid the money received.
rcp_amount	Number	n/a	No	The amount received.
rcp_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.

### exp\_referral

Field Name	MS Access Data Type	Length	Required ?	Description/Comment
rfr_pk	Text	38	Yes	Not used by the import process; only useful for user reference.
rfr_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
rfr_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
rfr_referred_to	Text	38	Yes	Code for the agency to which the referral was made. This field will be used for both internal and external referrals. The master list, which combines internal and external providers, is created and maintained by the central administrator.
rfr_service_category	Text	38	Yes	Code representing a service category as defined by HRSA for the 2007 CADR.
rfr_date_referred	Date/Time	n/a	Yes	The date on which the referral was made.
rfr_status	Text	38	Yes	Code for: <ul style="list-style-type: none"> <li>• 01 - Pending</li> <li>• 02 - Completed</li> </ul>

				<ul style="list-style-type: none"> <li>● 03 - Lost to follow up</li> <li>● 04 - Rejected</li> </ul>
rfr_date_received	Date/Time	n/a	No	The date on which the referred service was provided.
rfr_class	Text	38	No	Code for a customizable list of referral classes. The master list is created and maintained by the central administrator.
rfr_comment	Text	255	No	Free text that can be used to supply additional information about the referral.
rfr_referred_to_label	Text	60	No	See rfr_referred_to, above. This label field is not required, but the code field is.
rfr_class_label	Text	60	No	See rfr_class above. This label field is not required, but the code field is.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.
rfr_service_category_label	Text	255	No	Code for: <ul style="list-style-type: none"> <li>● 001 - Outpatient/Ambulatory Medical Care</li> <li>● 002 - Oral Health Care</li> <li>● 003 - Mental Health Services</li> <li>● 004 - Substance Abuse: Outpatient</li> <li>● 005 - Face-to-face Case Management</li> <li>● 006 - Other Case Management (non face-to-face)</li> <li>● 007 - Rehabilitation Services</li> <li>● 008 - Home Health: Professional Care</li> <li>● 009 - Home Health: Para-Professional Care</li> <li>● 010 - Home Health: Specialized Care</li> <li>● 011 - Hospice Services</li> <li>● 012 - Buddy/Companion Service</li> <li>● 013 - Client Advocacy</li> <li>● 014 - Respite Care</li> </ul>

				<ul style="list-style-type: none"> <li>● 015 - Emergency Financial Assistance</li> <li>● 016 - Housing Services</li> <li>● 017 - Food Bank/Home-delivered Meals</li> <li>● 018 - Medical Transportation Services</li> <li>● 019 - Service Outreach</li> <li>● 020 - Other Counseling (not mental health)</li> <li>● 021 - Permanency Planning</li> <li>● 022 - Health ed./risk reduction/prevention</li> <li>● 023 - Other support services</li> <li>● 024 - Treatment Adherence Counseling</li> <li>● 025 - Medical Nutrition Therapy</li> <li>● 026 - Child Care Services</li> <li>● 027 - Child Welfare Services</li> <li>● 028 - Pediatric Developmental Assessment/Services</li> <li>● 029 - Psychosocial Support</li> <li>● 030 - Substance Abuse: Residential</li> <li>● 031 - Early Intervention (Part A - B)</li> <li>● 032 - Referral: Health Care/Supportive</li> <li>● 033 - Referral: Clinical Research</li> <li>● 034 - Legal Services</li> <li>● 035 - Health Insurance Program (HIP)</li> <li>● 036 - ADAP Insurance</li> <li>● 037 - AIDS Pharmaceutical Assistance</li> <li>● 038 - Home Health Care</li> </ul>
--	--	--	--	---

				<ul style="list-style-type: none"> <li>● 039 - Home and Community-based Health Services</li> <li>● 040 - Medical Case Management</li> <li>● 041 - Case Management (non-medical)</li> <li>● 042 - Linguistics Services</li> <li>● 800 - Non CARE Act Service</li> </ul>
rfr_status_label	Text	255	No	Code for: <ul style="list-style-type: none"> <li>● 01 – Pending</li> <li>● 02 - Completed</li> <li>● 03 – Lost to follow up</li> <li>● 04 – Rejected</li> </ul>

### exp relations

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
rt_pk	Text	38	Yes	Uniquely identifies each record.
rt_index_cln_fk	Text	38	Yes	FK to the index client in the relation.
rt_dependant_cln_fk	Text	38	Yes	FK to the dependant client in the relation.
rt_relation_fk	Text	38	Yes	Code for the relation the dependant client has with the index client.
rt_relation_label	Text	50	No	Descriptive label to help with matching.
rt_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.

### exp service

Field Name	MS Access Data Type	Length	Required ?	Description/Comment
srv_pk	Text	38	Yes	Not used by the import process; only useful for user reference.
srv_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
srv_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
srv_subservice	Text	127	Yes	Code for the description of the service provided to the client. The master list

				is created and maintained by the central administrator.
srv_date	Date/Time	n/a	Yes	Date of service provided
srv_quantity	Single	n/a	No**	Number if service units
srv_price	Currency	n/a	No***	Unit price. CAREWare multiplies this times quantity to calculate a total.
srv_subservice_label	Text	176	No	Descriptive label for Service code, primarily used in the CAREWare PDE
srv_contract_name	Text	50	No	Specifies which contract the service is attached to. NOTE: An error will occur if a value is provided and it does not match a valid contract name.
srv_category	Text	100	No	Label for the service category to which this service entry belongs. *This field is not imported*
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.

\* All Boolean fields are required by CAREWare. Any left null will be interpreted as FALSE.

\*\* The quantity field defaults to 1 if no value is supplied.

\*\*\* Price defaults to \$0 if no values are supplied.

\*\*\*\*Deprecated

### exp test

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
tst_pk	Text	38	Yes	Uniquely identifies each record.
tst_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
tst_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
tst_test_definition_code	Text	38	Yes	Code for the specific type of test. The master list is created and maintained by the central administrator.
tst_date	Date/Time	n/a	Yes	Date of the test. (This is usually the date the specimen was collected)
tst_comment	Memo	n/a	No	Free text that can be used to supply additional information about the test.
tst_result	Text	72	Yes	Code for a qualitative test result. This is a customizable list of result codes. Note: if an operator is included in the result, it is expected to be one of the following: Acceptable values are: <ul style="list-style-type: none"> <li>• "&lt;"</li> <li>• "&lt;="</li> </ul>

				<ul style="list-style-type: none"> <li>• “=”</li> <li>• “&gt;=”</li> <li>• “&gt;”</li> </ul>
tst_titer	Text	10	No	Include if the test produces a titer result.
tst_test_definition_label	Text	50	No	Descriptive label for Test code, primarily used in the CAREWare PDE.
tst_action_code	Text	38	No	Code for Action taken for this test. Will be mapped to a CAREWare test action.
tst_action_label	Text	200	No	Descriptive label for action.
prv_name	Text	60	No	Added to allow importing data from multiple domains in a single file; prv_name acts as a referential key to the provider for each record.

\* All Boolean fields are required by CAREWare. Any left null will be interpreted as FALSE.

### exp vital sign

Field Name	MS Access Data Type	Size	Req.?	Description/Comment
vtl_sg_pk	Text	38	No	Uniquely identifies each record.
vtl_sg_cln_fk	Text	38	Yes	Points to the client record to which this record is related.
vtl_sg_delete	Yes/No	n/a	No*	Yes if this record has been deleted at the provider and should be deleted in CAREWare.
vtl_sg_date	Date/Time	n/a	Yes	Date the value was recorded.
vtl_sg_vital_name	Text	50	No	Code for the type of value recorded in each record. Valid values: <ul style="list-style-type: none"> <li>• Height</li> <li>• Weight</li> <li>• Pulse</li> <li>• Systolic</li> <li>• Diastolic</li> <li>• Temperature</li> <li>• NumVisits</li> <li>• NumHospitalDays</li> <li>• NumERVisits</li> </ul>
vtl_sg_value	Number	n/a	No	Recorded value for the specified vital sign.
vtl_sg_notes	Text	75	No	Additional notes for this record.

## Appendix A: Creating an encrypted URN (EURN)

CAREWare uses the URN32.dll (a standard Windows 32 bit dll that needs to be installed in the Windows system folder) to encrypt a client's URN and create a value for EURN. Here is some sample VB.NET code for how to use this dll to create an EURN:

```
' ## This code is part of CAREWare and is copyright, Jeff Murray's Programming Shop, Inc. (jProg).
' ## It is protected under US and international copyright laws and is provided only as a
' ## supplement to jProg's CAREWare. This code is provided as is without warranty of any kind,
' ## either express or implied, including but not limited to implied warranties of fitness for a
' ## particular purpose or merchantability.
' ## By providing this code, jProg grants a limited, nonexclusive license to distribute or modify
' ## this code solely for use in connection with CAREWare. This code is not to be used, modified,
' ## or distributed for any purpose other than to facilitate the use of CAREWare pursuant to a
' ## duly issued CAREWare license.

' ##MODULE_SUMMARY This object exposes a shared function that encrypts URNs.
Public Class jURNEncryption

'URN32.DLL has an function called MDString.
'You pass it string containing the URN and it returns
'the encrypted value
Declare Sub MDString Lib "URN32.DLL" (ByVal UURN As String)

' ## Encrypt the supplied URN.
' ##PARAM URN URN to encrypt.
' ##RETURNS Encrypted URN.
Public Shared Function EncryptURN(ByVal URN As String) As String

'Declare a string to send
Dim EncryptedURN As String

'If the URN ends in a U, trim the U for backward
'compatibility with other systems that don't use the U
'note: the U stands for Unique and was added with CW 4.0
If URN.Substring(URN.Length - 1, 1) = "U" Then
EncryptedURN = URN.Substring(0, 11)
Else
'If the last character is other than a U, then
'we can't be backwards compatible or it would cause
'a duplicate
EncryptedURN = URN
End If

'Call MDString in URN32.DLL
MDString(EncryptedURN)

'The original specification called for it to be no longer than
'9 characters, but sometimes it gets liberal with that
Return Left(EncryptedURN, 9)

End Function

End Class
```

## Appendix B: Using the template mdb to create Encrypted URNs (EURN) for clients

If an exporter desires to exclude client names from the export this is allowed, but then each client MUST have a value for the EURN field. This can be done programmatically (see [Appendix A](#)) or from within the template mdb file. Exporters can use this functionality to generate the EURNs and then remove the client names before sending the export file.

In order to use the Template file to create the EURNs, the following criteria must be met:

- ✓ The computer must have the file URN32.dll in the appropriate Windows system folder (for example, in Windows XP it should be in C:\WINDOWS\system32).
- ✓ The CAREWare values for gender must be used for the column cln\_gender:
  - 1 – Male
  - 2 – Female
  - 3 – Transgender
  - 4 – Transgender MtF
  - 5 – Transgender FtM
  - 6 – Refused to Report
  - 9 – Unknown
- ✓ Note also that this functionality assumes the values for date of birth (cln\_dob) are dates in the format mm/dd/yyyy.

Once these are met, to use the functionality:

- 1) Populate the client records with all information, including the URN-related fields in the client records (First Name, Last Name, Gender and DOB).
- 2) From inside the template press Ctrl-E to execute the macro that will create the EURN values for all clients. Note that if a client is missing any of the 4 fields that are used to create the EURN, the EURN will be left blank and this client record will be logged as an error during the export.
- 3) Once the EURNs are created, the exporter has the option of removing the first and last names of the clients. There is a macro built into the template that will automatically delete the first and last name for all clients – just press Ctrl-D to clear out those fields from within the database.

The export file will now have correct EURN values for the clients. Remember that DOB and Gender are always required.

## Appendix C: Medication Frequency Codes

Frequency	Multiplier *	Description
qd	1	Every day ( <i>quaque die</i> )
bid	2	Twice a day ( <i>bis in die</i> )
tid	3	Three times a day ( <i>ter in die</i> )
qid	4	Four times a day ( <i>quater in die</i> )
prn	<none>	As Necessary ( <i>pro re nata</i> )
qw	0.1428571	Once a Week (q = <i>quaque</i> )
biw	0.2857143	Biweekly
tiw	0.4285714	Three Times in a Week
qow	0.0714285	Every Other Week
qod	0.5	Every Other Day
qh	24	Every Hour ( <i>quaque hora</i> )
qhs	1	Every Bedtime ( <i>quaque hora somni</i> )
qm	1	Every Morning
q6h	4	Every 6 Hours
q12h	2	Every 12 Hours

\* The Multiplier is a translation of the frequency into a number that indicates times per day